

1. LAY 5 - 4' - 2 X 10'S, BEST SIDE DOWN ON A FLAT CLEAN SURFACE WITH 22 - 1/4" X 2" CARRIAGE INSERTED. SQUARE AND SPACE BOARDS WITH A 1/4" GAP BETWEEN BOARDS.

8

9

10

11

12

38

10

48

4

4

- 2. ATTACH END FRAMES TO PLANKS AND HAND TIGHTEN HARDWARE.
- 3. ATTACH 23" DIAGONAL BRACES FROM FRAME TO CENTER BOARD. USE 1" CAP SCREW WITH NUT AND 2" CARRIAGE BOLT WITH NUT TO ATTACH.
- 4. ATTACH OUTRIGGER FRAME TO END FRAME USING 1" HEX BOLTS. NOTE: THERE ARE RIGHT AND LEFT OUTRIGGER FRAMES AS MARKED.

1" X 5/16" HEX HEAD CAP SCREWS, SST

5/16 SERRATED FLANGE NUTS, SST

1/4" SERRATED FLANGE NUTS, SST

2" X 1/4" CARRIAGE BOLTS, SST

- 5. ATTACH CLAMP ASSEMBLIES AT THE FOUR CORNERS TO SECURE THE OUTRIGGER TO THE END FRAMES.
- 6. ATTACH SEATS TO FRAMES WITH 2" CARRIAGE BOLTS AND NUTS.
- 7. TIGHTEN ALL HARDWARE.

SCALE:	NONE		11 GAUGE SQUARE PICNIC TABLE
DATE DRAWN:	31-09	APPROVED BY:	ASSEMBLY
DRAWN BY:	CHG		
DATE REVISED:			RECYCLED PLASTIC TOP & SEATS
REVISED BY:		DATE:	RECICLED LEASTIC TOT & SEATS
			I